



**IMPORTANT NOTE:** When installing VELFAC windows and accessories, please ensure full compliance with national building regulations and British/European standards where necessary. This drawing is for guidance only and both the designer and installer must be satisfied that the principles outlined in this drawing are effectively transposed to suit project requirements and unique site conditions & limitations.

All dimensions are in millimetres where shown. Do not scale.

**NOTES:**

1. Detail assumes that all forms of differential deflection are contained within the structure and not allowed to transmit to the VELFAC system. If differential deflection is expected then please consult with VELFAC for project specific interfaces
2. External weather seal to be either Tremco-Ilbruck TP600 impregnated joint sealing tape sized to suit finished joint size or ARBOSIL 1090 silicone seal and polyethylene backing rod
3. Fixings and lugs to be installed strictly in accordance with VELFAC installation guidance.
4. Fixing grounds must be able to withstand all loads transmitted from and through the VELFAC system

primary weather line

primary air barrier line



Rev	Date	By	Description
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

**VELFAC** Ltd

tel: +44 1223 897100  
 fax: +44 1223 897101  
 email: post@VELFAC.co.uk  
 web: www.VELFAC.co.uk

Title:  
**VELFAC 200 SYSTEM - triple glazed  
 TYPICAL CILL DETAIL**  
 insulated render/timber frame

Scale: 1:2 approx. @ A4	Project no: -
Date: August 2015	Drawing no: -
Drawn: Studio62	V.200.TGU.02.B.C.001
Checked: -	Revision: -





